

A Reliable Operation & Performance Solution that fits your needs



Ethernet



USB

Features

- Direct Thermal Printing, No Ink or Cartridge required.
- 80mm thermal printer with Manual Paper cutter function, Interface: USB+LAN
- Low Cost and clear printing, print speed can reach to 160mm/s.
- Up to 60 Kms Head Life, Support Window software based on ESC/POS command.

| | |
|---------------------------------|---|
| Printing | |
| Printing Method | Thermal Line |
| Printing width | 72mm |
| Resolution | 576 Dots/Line Or 512 Dots/Line(8dots/mm,203dpi) |
| Printing Speed | 160mm/s |
| Interface | USB+LAN |
| Line Space | 3.75mm(Can adjust line space by command) |
| Line No | Font A-32 Lines/Font B-42 Lines/Simple |
| Power | |
| Input | AC 110V/220V,50~60Hz |
| Output | DC 24V/2.5A |
| Cash Drawer output | DC 24V/1A |
| Physical characteristics | |
| Weight | 1.15KG |
| Dimension | 195*140*148(MM) |
| Environment | |
| Working: Temp | 5 ~ 45°C, Humidity:10 ~ 80% |
| Storage: Temp | -10 ~ 50°C ,Humidity:10 ~ 90%(No dew) |
| Reliability Parameter | |
| Print Head Life | 60-80KM(print density≤12.5) |
| Cutter Life | No Cutter |
| Software | |
| Driver | Linux,WinXP,Win7,Win8,Win8.1, Win 10 |



Paper Guard Plate



USB



Adaptor



80MM Paper