



www.PegasusTech.net

Pegasus PS5161

Wired 2D Barcode Scanner

Deliver unmatched Scanning Performance

Industries

Retail



Healthcare



Warehouse



Logistics



Transport



Manufacture



Overview :

Pegasus PS5161 is new design 2D wired Barcode scanner which is very high cost-effective, support various barcodes, such as damaged, blurred, scratched, malposed, colorful, fuzzy Barcodes and is widely used in various industries.

Features :

- Wire Life is more durable.
- High-performance CMOS imaging technology.
- Plug and play, easy to operate and match quickly.
- Scanning code is fast and accurate, high cashier efficiency.
- New decoding chip can interpret various 1D and 2D barcode.



www.PegasusTech.net

Specification Sheet

Industries

Retail



Healthcare



Warehouse



Logistics



Transport



Manufacture



Performance Parameters	
Light Sources	617nm LED Aimer, White LED
Supported Symbologies	1D: EAN-13, EAN-8, UPC-A, UPC-E, UPC-A, Code 39, Code 93, Code 32, Code 128, Codabar, Interleave 2 of 5, ISBN, ISSN, IATA 2 of 5, Industrial 2 of 5, MSI Plessey, Matrix 2 of 5. 2D: QR Code, Data Matrix, PDF417, Micor QR, Micor PDF417, Han xin Code, Dotcode.
Resolution	640*480CMOS
Scan Method	Manual/Continuous/Automatic inductive scanning
Scan Angle	Yaw 55°,Rotation 360°,Pitch 55°
Precision	≥5mil
Contrast	≥10%
Depth of scan field	EAN13 50-200MM(13MIL);QR 25 -240MM(20MIL);PDF147 30 -130MM (6.67MIL)
Error Rate	Less than 1/5million
Interface	USB-HID, USB-COM, RS232
Physical Parameters	
Dimensions	70.5mm*86.2mm*165.2mm
Weight	100g
Material	ABS+PC
Cable Length	1.8 Meter
Environmental Parameters	
Operating Temperature	-20°C ~50°C
Storage Temperature	-40°C~70°C
Relative Humidity	5%~95% RH (Non-condensing)
Electric Parameters	
Voltage	DC5V±5%
Operating Current	170mA
Standby Current	USB 25mA; RS232 2uA

