

Mobile products to supporting the use, and well-matched to outdoor work environments



iOS



Android



Wince CE



Bluetooth



Features

- Support 1D, 2D Barcode printing
- While compatible with Windows, Android and iOS system
- 2000 mAh big capacity battery, longer lasting time
- Smart power saving and power consumption control to ensure longer printing time
- Support USB COM and Bluetooth communication
- Support sound and light reminder when lack of paper, printing abnormal
- Anti fall of 1.5M cement floor

Print Parameter	Printing Method	Thermal Line
	Effective Printing Width	48mm
	Resolution	384 dots/line (8dots/mm, 203dpi)
	Printing Speed	70mm/S
	Interface	USB, Serial, Bluetooth
	Line spacing	3.75mm (Can adjust line spacing by command)
	Line No.	Font A:32 character/Line Font B:42 character/Line Simple/Traditional Chinese-16 lines
	Character	The standard GB18030 simplified / traditional Chinese characters library
Barcode Character	Character Size	ANK character, Font A : 1.5×3.0mm (12×24 dots) Font B : 1.1×2.1mm (9×17 dots) Simplified/Traditional : 3.0×3.0mm(24×24 dots)
	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/ WestEurope/Greek/Hebrew/EastEurope/Iran/ WPC1252/PC866/PC852/PC858/IranII/Latvian/ Arabic/PT151,1251/PC737/WPC/1257/ Thai/Vietnam/PC864/PC1001/(Latvian)/ (PC1001)/(PT151,1251)/(WPC1257)/(PC864)/ (Vietnam)/(Thai)
Barcode	Barcode	1D.Bar code : UPC-A/UPC- E/JAN13(EAN13)/ JAN8(EAN8)CODE39/ITF/ CODABAR/ CODE93/ CODE128 2D.Bar code : QRCODE
	Graphics printing	Supports bitmap download and print (support each bitmap size Max.8K, download up to 5pcs)
Power saving Mode	Smart power saving	Support
	Variable speed printing	Support
	Consumption	Support
	Dormancy	Support
Detection	Sensor	Lack of paper detection
Indicator	Power Display	Support
	Charge Indicator	Support
	Lack of paper	Support
	Beep	Lack of paper, printing abnormal alarm
Paper	Type	Thermal
	Width	57.5±0.5mm
	thickness	≤0.12mm
	Diameter	≤40mm
	Feed	Easy (Clamshell feed)
Commands	Commands	ESC/POS
Power	Type	Rechargeable Lithium polymer battery
	Capacity	2000mAh/7.4V
	Charger	9.0V/2A
Buffer	Input	4KB
	NV Flash	40KB
Physical features	Weight	224gm
	Dimension	114*80*50mm
Environment	Operating	Temp : 5 ~ 45°C, Humidity : 10 ~ 80%
	Storage	Temp : -10 ~ 50°C , Humidity : 10 ~ 90% (No Dew)
Reliability	Print head life	50KM (Printing Density≤12.5)
Software	Driver	Win2000,Win2003,WinXP,Win7,Win8,Win8.1
	SDK and Programing Manual	Android, IOS, Linux

Note:- This product required software development skill to integrate with android app and iOS app, Programming Guide included in CD or downloadable from Manufacture website.